# 2014 LEHR PROPANE OUTBOARD PRODUCT INFORMATION GUIDE

# 2.5 HP Propane Outboard

## **SPECIFICATIONS**

Models LP2.5S

Engine Type Propane Powered 4 Stroke OHV

Horsepower Rating 2.5 hp (1.8 kW)
Displacement 4.39 cu in / 72 cc

Bore X Stroke 2.12" X 1.37" / 54mm X 31.5mm

Cylinders 1

Full Throttle RPM Range 4500 - 5500 RPM Ignition System CDI Ignition Starting System Manual

Fuel Propane (110 Octane)
Carburetion No Choke / No Priming

Lubrication Wet Sump
Control System Tiller Handle
Exhaust System Above Propeller

Cooling System Water / Thermostatic Control

Trim Positions 5
Gear Shift F - N
Gear Ratio 2.08
Shaft Length 15" (S)

Standard Prop 7.25" X 6" 3 Blade Aluminum Weight LP2.5 S 37.4 lbs / 16.96 kg

**Fuel Tank Type** 

On Board Twist 'n Go 16.4 oz Propane

Canister

Remote(Optional) 11 lbs & 17 lbs Composite Tanks

Recommended Oil 4 Stroke 10W-30 Engine Oil Capacity 0.37 US qt (0.35L)

Warranty 3 Year Limited Warranty

C.A.R.B. Rating 3 Star Ultra Low

#### **FEATURES & BENEFITS**

> Propane Power 4 Stroke Engine Design - *clean, efficient, eco friendly propane power.* 

>Twist 'n Go Fueling - simply twist in a standard 16.4oz "camping" propane canister and go. Easy, no mess or spilling gas into the water while refueling.

> Remote Fuel Tank Capability - for increased range add a remote 5 gal "BBQ" tank. Lehr also offers 2 sizes of lightweight composite auxiliary tanks.

> F-N Gear Shift with 180° Steering and 360° Turning Radius - more reverse thrust & easy maneuverability

> Tiller Handle with Twist Grip Throttle - precise throttle control and steering.

> Throttle Friction Adjustment - *minimizes driver* fatigue.

> Steering Friction Adjustment - adjust steering tension to set and maintain direction.

> Auto Reverse Lock - user friendly & safety

> Easy Starting - features automatic decompression, with no choking or priming.

> Lightweight Compact Design with a convenient Rear Mounted Carrying Handle - easy handling.

>Stainless Steel Drive, Shift & Prop Shafts - user friendly maintenance and corrosion protection

> Emergency Stop Lanyard - user safety.

> Oil Level Sight Glass - user friendly

	PRICING			
LP2.5S	MSRP	\$1,259.99		
	MAP	\$1,049.99		

# 5.0 HP Propane Outboard

### **SPECIFICATIONS**

Models LP5.0S

LP5.0L

Engine Type Propane Powered 4 Stroke OHV

Horsepower Rating 5.0 hp (3.6 kW)
Displacement 6.83 cu in / 112 cc

Bore X Stroke 2.32" X 1.61" / 59 mm X 41 mm

Cylinders 1

Full Throttle RPM Range 4500 - 5500 RPM Ignition System CDI Ignition Starting System Manual

Fuel Propane (110 Octane)
Carburetion No Choke / No Priming

Lubrication Wet Sump
Control System Tiller Handle
Exhaust System Above Propeller

Cooling System Water / Thermostatic Control

Trim Positions 5

Gear Shift F - N - R Gear Ratio 2.08

Shaft Length 15" (S) 20" (L)

Standard Prop 7.5" X 7" 3 Blade Aluminum Weight LP5.0S 48 lbs / 21.8 kg

LP5.0L 52 lbs / 23.6 kg

**Fuel Tank Type** 

On Board Twist 'n Go 16.4 oz Propane

Canister

Remote (Optional) 11 & 17 lbs Composite Tanks

Recommended Oil 4 Stroke 10W-30 Engine Oil Capacity 0.53 US qt (0.5L)

Warranty 3 Year Limited Warranty

C.A.R.B. Rating 3 Star Ultra Low

	PRICING			
LP5.0S	MSRP	\$2,039.99		
	MAP	\$1,699.99		
LP5.0L	MSRP	\$2,075.99		
	MAP	\$1,729.99		

#### **FEATURES & BENEFITS**

> Propane Power 4 Stroke Engine Design - *clean, efficient, eco friendly propane power.* 

>Twist 'n Go Fueling - simply twist in a standard 16.4oz "camping" propane canister and go. Easy, no mess or spilling gas into the water while refueling.

> Remote Fuel Tank Capability - for increased range add a remote 5 gal "BBQ" tank. Lehr also offers 2 sizes of lightweight composite auxiliary tanks.

> F-N-R Gear Shift with 360° Turning Radius - more reverse thrust & easy maneuverability

>Shallow Water Drive - ability to run in shallow water

> Tiller Handle with Twist Grip Throttle - precise

throttle control and steering.

 $\verb| > Throttle Friction Adjustment - minimizes driver \\$ 

fatigue.

> Steering Friction Adjustment - adjust steering

tension to set and maintain direction.

> Auto Reverse Lock - user friendly & safety

> Easy Starting - features automatic decompression,

with no choking or priming.

> Lightweight Compact Design with a convenient

Rear Mounted Carrying Handle - easy handling.

> Stainless Steel Drive, Shift & Prop Shafts - user friendly maintenance and corrosion protection

> Emergency Stop Lanyard - user safety.

# 9.9 HP Propane Outboard

# **SPECIFICATIONS**

Remote (Optional)

**Recommended Oil** 

**Engine Oil Capacity** 

Warranty

C.A.R.B. Rating

<u>SPECIFICATIONS</u>	
Models	LP9.9S (Manual Start, Tiller) LP9.9L (Manual Start, Tiller) LP9.9ES (Electric Start, Tiller) LP9.9ES-IB (Electric Start, Tiller) LP9.9EL (Electric Start, Tiller) LP9.9EL-IB (Electric Start, Tiller) LP5.0ERS (Electric Start, Remote) LP9.9ERL (Electric Start, Remote)
Engine Type Horsepower Rating Displacement Bore X Stroke Cylinders Full Throttle RPM Range Ignition System Starting System Fuel Carburetion Lubrication Control System Exhaust System Cooling System Trim Positions Gear Shift Gear Ratio Alternator Output  Shaft Length Standard Prop Weight	Propane Powered 4 Stroke SOHC  9.9 hp (7.2 kW)  12.94 cu in / 212 cc  2.29" X 1.69" / 56 mm X 43 mm  2  4500 - 5500 RPM  CDI Ignition  Manual or Electric (E)  Propane (110 Octane)  No Choke / No Priming  Wet Sump / Pressure Lubricated  Tiller Handle or Remote  Through Prop  Water / Thermostatic Control  5  F - N - R  2.08  6 amp / 80 watt - Electric  6 amp / 80 watt - Manual  (Manual requires optional regulator)  15" (S) 20" (L)  8" X 8.5" 3 Blade Aluminum  LP9.9S 88 lbs / 39.8 kg  LP9.9L 92 lbs / 41.7 kg  LP9.9ES 98 lbs / 44.5 kg  LP9.9ES 98 lbs / 44.5 kg
	LP9.9ES-IB 100 lbs / 45.4 kg LP9.9EL 102 lbs / 46.3 kg LP9.9EL-IB 104 lbs / 47.2 kg LP9.9ERS 96 lbs / 43.5 kg LP9.9ERL 100 lbs / 45.4 kg
Fuel Tank Type	

11 & 17 lbs Composite Tanks

3 Year Limited Warranty

4 Stroke 10W-30

0.85 US qt (0.8L)

3 Star Ultra Low

31 lbs Liquid Draw Composite Tanks

#### **FEATURES & BENEFITS**

- > Propane Power 4 Stroke Engine Design *clean, efficient, eco friendly propane power.*
- > Remote Fuel Tank Capability Lehr also offers 3 sizes of lightweight composite auxiliary tanks.
- > Lightweight Compact Design with a Convenient Carrying Handles easy handling.
- > Forward Mounted Gear Shift convenient location
- >Electric Start Models easy fingertip starting
- >New Internal Battery Electric Start Tiller Models See separate page for all the features & benefits
- > F-N-R Gear Shift easy maneuverability
- > Tiller Handle with Twist Grip Throttle *precise* throttle control and steering.
- > Throttle Friction Adjustment *minimizes driver* fatigue.
- > Steering Friction Adjustment adjust steering tension to set and maintain direction.
- >Shallow Water Drive ability to run in shallow water
- > Stainless Steel Drive, Shift & Prop Shafts *user* friendly maintenance and corrosion protection
- >Low Oil Pressure Warning System alerts operator By providing visual warning

	PRICING		
Model	MSRP	MAP	
LP9.9S	\$3,119.99	\$2,599.99	
LP9.9L	\$3,155.99	\$2,629.99	
LP9.9ES	\$3,599.99	\$2,999.99	
LP9.9ES-IB	\$3,959.99	\$3,299.99	
LP9.9EL	\$3,635.99	\$3,029.99	
LP9.9EL-IB	\$3,995.99	\$3,329.99	
LP9.9ERS #	\$3,563.99	\$2,969.99	
LP9.9ERL#	\$3,599.99	\$2,999.99	
NOTE (#) - Remote Control is priced seprerately			

## **15 HP Propane Outboard**

### **SPECIFICATIONS**

Models	LP15S	(Manual Start, Tiller)
	LP15L	(Manual Start, Tiller)
	LP15ES	(Electric Start, Tiller)
	LP15ES-IB	(Electric Start, Tiller)
	LP15EL	(Electric Start, Tiller)
	LP15EL-IB	(Electric Start, Tiller)
	LP15ERS	(Electric Start, Remote)
	LP15ERL	(Electric Start, Remote)

Engine Type Propane Powered 4 Stroke SOHC

Horsepower Rating 15 hp (11 kW)
Displacement 19.7 cu in / 323 cc

Bore X Stroke 2.32" X 2.32" / 59 mm X 59 mm

Cylinders 2

Full Throttle RPM Range 4500 - 5500 RPM Ignition System CDI Ignition

Starting System Manual or Electric (E)
Fuel Propane (110 Octane)
Carburetion No Choke / No Priming

Lubrication Wet Sump / Pressure Lubricated

Control System Tiller Handle or Remote

Exhaust System Through Prop

Cooling System Water / Thermostatic Control

Trim Positions 5
Gear Shift F - N - R
Gear Ratio 2.08

Alternator Output 6 amp / 80 watt - Electric 6 amp / 80 watt - Manual

(Manual requires optional regulator)

Shaft Length 15" (S) 20" (L)

 Standard Prop
 9.5" X 11"
 3 Blade Aluminum

 Weight
 LP15S
 110 lbs / 49.9 kg

 LP15L
 114 lbs / 52.0 kg

 LP15ES
 120 lbs / 54.4 kg

 LP15ES-IB
 122 lbs / 55.3 kg

 LP15EL
 124 lbs / 56.2 kg

 LP15EL-IB
 126 lbs / 57.2 kg

LP15ERS 126 lbs / 53.5 kg
LP15ERL 122 lbs / 55.3 kg

Fuel Tank Type 31 lbs Liquid Draw Composite Tanks

Recommended Oil 4 Stroke 10W-30 Engine Oil Capacity 1.06 US qt. (1.0L)

Warranty 3 Year Limited Warranty


C.A.R.B. Rating 3 Star Ultra Low

#### **FEATURES & BENEFITS**

- > Propane Power 4 Stroke Engine Design clean, efficient, eco friendly propane power.
- > Remote Fuel Tank Capability Lehr also offers 3 sizes of lightweight composite auxiliary tanks.
- > Lightweight Compact Design with a Convenient Carrying Handles *easy handling*.
- > Forward Mounted Gear Shift convenient location
- >Electric Start Models easy fingertip starting
- >New Internal Battery Electric Start Tiller Models -See separate page for all the features & benefits
- > F-N-R Gear Shift easy maneuverability
- > Tiller Handle with Twist Grip Throttle *precise* throttle control and steering.
- > Throttle Friction Adjustment *minimizes driver* fatigue.
- > Steering Friction Adjustment adjust steering tension to set and maintain direction.
- >Shallow Water Drive ability to run in shallow water
- > Stainless Steel Drive, Shift & Prop Shafts user friendly maintenance and corrosion protection
- > Low Oil Pressure Warning System alerts operator By providing visual warning

	PRICING		
Model	MSRP	MAP	
LP15S	\$3,515.99	\$2,929.99	
LP15L	\$3,551.99	\$2,959.99	
LP15ES	\$3,995.99	\$3,329.99	
LP15ES-IB	\$4,355.99	\$3,629.99	
LP15EL	\$4,031.99	\$3,359.99	
LP15EL-IB	\$4,391.99	\$3,659.99	
LP15ERS #	\$3,959.99	\$3,299.99	
LP15ERL#	\$3,995.99	\$3,329.99	
NOTE (#) - Remote Control is priced seprerately			

# NEW FOR 2014 THE WORLD'S FIRST ELECTRIC START PORTABLE OUTBOARD MOTOR WITH A SELF ENCLOSED INTERNAL BATTERY FOR STARTING YOUR ENGINE



- Your portable outboard remains portable. No rigging or clutter in your boat.
- Weighs less than 2 pounds making it 70% to 80% lighter than a traditional lead acid battery.
- Lithium Iron batteries are able to hold an unloaded charge for an entire year without compromising service life.
- Life span is up to twice as long as a lead acid battery
- Dry & Sealed No maintenance or hazardous materials to worry about.
- Extremely low discharge rate making it an ideal choice for seasonal use.
- Recharges while you are running your engine.
- Three Year Warranty

	Available in 4 models
LP9.9ES-IB	(15" Shaft Length, Electric Start, Internal Battery, Tiller)
LP9.9EL-IB	(20" Shaft Length, Electric Start, Internal Battery, Tiller)
LP15ES-IB	(15" Shaft Length, Electric Start, Internal Battery, Tiller)
LP15EL-IB	(20" Shaft Length, Electric Start, Internal Battery, Tiller)

## LEHR PROPANE POWERED OUTBOARD FUEL CONSUMPTION TESTS

NOTE: All times are approxiximate and may vary based on the size and type of boat, wind, current and other factors.

ENGINE MODEL	Gallons per Hour	16.4oz Camping Bottle	11 lb (2.6 gallon) Composite Tank	17 lb (4.0 gallon) Composite Tank	20 lb (5 gallon) Standard Tank	31 lb (7.5 gallon) Liquid Draw Composite Tank
	T	<u> </u>	,			,
LP2.5						
@5000 RPM	.24 gal/hr	1 HR	11 HRS	17 HRS	20 HRS	N/A
@3000 RPM	.10 gal/hr	2.5 HRS	26 HRS	40 HRS	48 HRS	N/A
LP5.0						
@5000 RPM	.50 gal/hr	30 mins	5 HRS	8 HRS	10 HRS	N/A
@3000 RPM	.22 gal/hr	1.4 HRS	12 HRS	18 HRS	22 HRS	N/A
LP9.9						
@5000 RPM	1 gal/hr	N/A	2.5 HRS	4 HRS	5 HRS	7.5 HRS
@3000 RPM	.44 gal/hr	N/A	6 HRS	9 HRS	11.4 HRS	17 HRS
LP15						
@5000 RPM	1.5 gal/hr	N/A	N/A	N/A	N/A	5 HRS
@3000 RPM	.66 gal/hr	N/A	N/A	N/A	N/A	11.4 HRS

Note: Propane weighs 4.2 lbs per gallon

## PROPANE ADVANTAGES

**POWERFUL** 

4-STROKE ENGINE
110 OCTANE FUEL
MORE EFFICIENT THAN 87 OCTANE GAS
MORE COST EFFECTIVE THAN GASOLINE
NO DEPENDENCE ON HIGH PRICED FOREIGN OIL
USA IS A PROPANE EXPORTER

ECO FRIENDLY

ZERO EVAPORATIVE EMISSIONS
PROPANE IS NOT A MARINE POLLUTANT

**EASY START** 

NO CHOKE
NO PRIMING
NO CARBURETOR GUM-UP
NO WINTERIZATION

**ECONOMICAL** 

MORE COST EFFECTIVE TO USE & MAINTAIN

**MULTIPLE FUELING OPTIONS** 

TWIST 'N GO 16.4oz PROPANE CANISTER OPTIONAL REMOTE LIGHTWEIGHT COMPOSITE PROPANE TANKS

**EASY TO TRANSPORT** 

LIGHTWEIGHT
NO LEAKING OF FUEL

NO WORRIES ABOUT FUEL QUALITY

**NO ETHANOL ISSUES OR STORAGE ISSUES**