

# MARINENAV

(902) 838-7011 | [www.marinenav.ca](http://www.marinenav.ca)

**Built North Atlantic Tough  
Trusted Everywhere**



## Bridgeview 12/15/19/22

Built on the same proven platform as our CG Elite monitors, Bridgeview LCD monitors offer excellent value and **daylight readable performance**. Available in **sizes from 12" to 22"** and with either **AC or DC power input**, Bridgeview monitors are the perfect choice for all of your display needs. Standard features include marine grade aluminum construction, **one-touch input selection** and **red monochrome night mode and dedicated backlit front controls**. For quality and reliability, MarineNav displays can't be beat! All of our marine displays are backed with a standard 2 year warranty. **Available with optional integrated computer** (15", 19" and 22" models only).



### OPTIONAL INTEGRATED COMPUTER FEATURES

- 1.2 GHz 64-bit processor
- 4 GB DDR3 RAM
- 60 GB Solid State storage
- 2 USB 2.0 ports
- Field swappable unit
- VGA and HDMI connections allow for dual displays
- Network port

# Bridgeview Display Specifications

Features	BV-12	BV-15	BV-19	BV-22
LCD Display	12.1" TFT Active Matrix Panel, LED backlight	15" TFT Active Matrix Panel, LED backlight	19" TFT Active Matrix Panel, LED backlight	22" TFT Active Matrix Panel, LED backlight
Integrated Computer	Not available	Available option	Available option	Available option
Brightness	1000 nit	1000 nit	700 nit	800 nit
Contrast	1000:1	1500:1	1500:1	1000:1
Resolution	1024 x 768 native	1024 x 768 native	1280 x 1024 native	1680 x 1050 native
Optimized Multi-Resolution	Up to 1920 x 1200 supported	Up to 1920 x 1200 supported	Up to 1920 x 1200 supported	Up to 1920 x 1200 supported
View Angle	160(H), 160(V)	160(H), 160(V)	170(H), 170(V)	170(H), 170(V)
Display Colours	262K	16.7 Million	16.7 Million	16.7 Million
Temperature	-10 to 55C Operating -20 to 70C Non-Operating	-10 to 55C Operating -20 to 70C Non-Operating	-10 to 55C Operating -20 to 70C Non-Operating	0 to 50C Operating -20 to 60C Non-Operating
Video Inputs	2 VGA, 2 HDMI optional DVI, 4 Composite	2 VGA, 2 HDMI optional DVI, 4 Composite	2 VGA, 2 HDMI optional DVI, 4 Composite	2 VGA, 2 HDMI optional DVI, 4 Composite
Other Inputs	Power, Serial	Power, Serial	Power, Serial	Power, Serial
Input Power	9~36V DC input	9~36V DC input 100~240V AC input	9~36V DC input 100~240V AC input	9~36V DC input 100~240V AC input
Power Consumption	35~40 watts	40 watts	50 watts	60 watts
Dimming	Wide dimming range to black	Wide dimming range to black	Wide dimming range to black	Wide dimming range to black
Picture-in-Picture	Yes	Yes	Yes	Yes
Bezel & Rear Case	High grade marine aluminum	High grade marine aluminum	High grade marine aluminum	High grade marine aluminum
Finish	Salt rated, UV protected powder coating	Salt rated, UV protected powder coating	Salt rated, UV protected powder coating	Salt rated, UV protected powder coating
Window & Enclosure Options	Standard matte front panel, optional optical bonded front panel, optional IP65 from front and/or rear	Standard matte front panel, optional optical bonded front panel, optional IP65 from front and/or rear	Standard matte front panel, optional optical bonded front panel, optional IP65 from front and/or rear	Standard matte front panel, optional optical bonded front panel, optional IP65 from front and/or rear
Backlit Front Controls	Yes, with one-touch hotkeys	Yes, with one-touch hotkeys	Yes, with one-touch hotkeys	Yes, with one-touch hotkeys
Bezel Dimensions	312 mm x 262 mm (12.28" x 10.31")	382 mm x 315 mm (15.04" x 12.40")	455 mm x 400 mm (17.91" x 15.75")	553 mm x 400 mm (21.77" x 15.75")
Chassis Dimensions	294 mm x 244 mm (11.57" x 9.60")	366 mm x 299 mm (14.41" x 11.77")	439 mm x 384 mm (17.28" x 15.12")	537 mm x 384 mm (21.14" x 15.12")
Install Depth	63 mm (2.49")	78 mm (3.07")	78 mm (3.07")	58 mm (2.28")
Installation Options	Console flush mount, VESA 75	Console flush mount, VESA 75	Console flush mount, VESA 75	Console flush mount, VESA 100
FCC Approved	Yes	Yes	Yes	Yes
Video Detection/Scaling	Yes	Yes	Yes	Yes
Warranty	2 year (2nd year with registration)	2 year (2nd year with registration)	2 year (2nd year with registration)	2 year (2nd year with registration)

MarineNav displays are available in a variety of sizes to provide for maximum flexibility. Please contact us or visit our website at [www.marinenav.ca](http://www.marinenav.ca) for more details.

**MARINE NAV**  
ISO 9001:2008 certified company

Panmure Island Wharf  
1466 Panmure Island  
Montague, PE, C0A 1R0  
(902) 838-7011  
[info@marinenav.ca](mailto:info@marinenav.ca)  
[www.marinenav.ca](http://www.marinenav.ca)

REV 05062013

Dealer Information

While we strive to ensure the accuracy of all items and descriptions in this document, this is not always possible. Specifications, options, and availability subject to change without notice. Errors and omissions excepted. We reserve the right to limit quantities.