

CHOOSING THE RIGHT ANTIFOULING PRODUCT

| ANTIFOULING | BOAT | RECOMMENDATION | TYPE |
|---------------|---|---------------------------------|------------------|
| NEO | All boats except aluminium Speed up to 25 knots | Moderate fouling water | Mixed matrix |
| ALLEGRO EXTRA | All boats except aluminium Speed up to 25 knots | Moderate to heavy fouling water | Self-eroding |
| AVISO | All boats except aluminium Speed up to 35 knots | Moderate to heavy fouling water | Hard matrix |
| ALUMAR SM | Reserved for aluminium boats All types of navigation | Aluminium only | Semi-hard matrix |
| PERFORMANCE | All boats except aluminium Speed up to 30 knots | Moderate fouling water | Hard matrix |

OUR CHOICE OF COLOURS

ANTIFOULING



FINISH



1. BLACK 2. VOLVO GREY-7119 3. WHITE 4. SEA GREEN-6373 5. ROYAL BLUE-5307 6. BRIGHT RED-3365 7. RED-BROWN-3331 8. NAVY BLUE-5304 9. MONASTRAL BLUE-5105 10. FLAG BLUE-5108 11. BASQUE BLUE-5111 12. SWIMMING POOL BLUE-5110 13. AZURE BLUE-5112 14. 'ETEL' GREEN-6175 15. LIGHT GREEN-6174 16. GRASS GREEN-6176 17. BUTTERCUP YELLOW-1146 18. ORANGE-1385 19. POPPY RED-3138 20. INDIAN RED-3137 21. BASQUE RED-3131 22. CLARET RED-3133 23. OLD WOOD-8166 24. 'OLÉRON' GREEN-6178 25. BRIGHT YELLOW-1147 26. IVORY-1157 27. 'BOSTON' WHITE-1151 28. WHITE 29. 'TRIANON' GREY-7118 30. PEARL GREY-7120 31. BLACK.

COMUS

2, rue Rol-Tanguy - 91180 Saint-Germain-lès-Arpajon
Tél : 33 (0)1 69 88 13 10 - Fax : 33 (0)1 60 84 04 81 - www.solutions-comus.com

The colours are presented for illustrative purposes and are not legally binding. Please refer to the PLASTICOQUE colour chart.



Do not litter.

COMUS[®]
M A R I N E

COMUS MARINE[®] SYSTEM

An innovation recommended by all types of hull.



ANTIFOULING / FINISH / MAINTENANCE

Le concentré de performance.

www.comus-marine.com

REVOLUTIONARY WATER-BASED SINGLE-PACK SYSTEM

DISCOVER THE MANY BENEFITS OF THE COMUS MARINE® SYSTEM

UNIVERSAL

Impossible to choose the wrong products, the system is suitable for all types of hull.

SINGLE-PACK

For easy implementation, no mixing required.

WATER-BASED

For improved environmental protection.

QUICK-DRYING

To save drying time between coats and for a quicker launch.

ODOURLESS

For greater application ease.



GUARANTEES EFFECTIVE PROTECTION IN 3 SIMPLE STEPS

PRIMER

BONDING & PROTECTING



PLASTIPRIM'O® *

Facilitates the bonding of all types of finish, including antifouling paints. Applicable in 1 to 2 coats onto all substrates: polyester, wood, steel, aluminium.

**If a filler coating is required, it must be applied between PLASTIPRIM'O and PLASTICOAT.*

PLASTICOAT®

Bond between the PLASTIPRIM'O primer and the PLASTILAQUE 180/127 finish and/or the antifouling paint. White and opacifying, PLASTICOAT conceals the micro-irregularities and coating touch-ups. Can be sanded to obtain a "bodywork" type finish and give optimal coverage and gloss to the lacquer finish.

UNDERCOAT

OPAQUE & UNIFORM



PLASTILAQUE 180®

Provides optimal gloss, finish and protection as well as great UV resistance. PLASTILAQUE 127 - solvent-based - also compatible with the Comus Marine system.

FINISH/ ANTIFOULING

PROTECTING & DECORATING



ANTIFOULING

Protects the hull below the waterline. NEO, PERFORMANCE, ALLEGRO EXTRA, AVISO and ALUMAR SM are formulated to respond to different types of application, depending on the boat and water fouling rate.