

# Reliability & efficiency down to a science.

Marine | RV | Industrial | Military | Street Lighting | Off-Grid

Get your money's worth with Genasun. This 50W 4A 12V MPPT controller is small, critically efficient, and cost-effective. The GV-4 extracts more power from any given panel than a PWM controller. And though PWMs may offer a lower controller cost, Genasun MPPT controller delivers more power - reducing the cost per watt by 10%-30% and giving you more bang for your buck. Its extremely low self-consumption makes it perfect for waiting out a few bad weeks of clouds.



**GV-4**

**4A @ 12V MPPT 50W**

- Marine grade
- No radio frequency noise
- Ultra-fast true MPP Tracking
- Excellent low-light performance
- Compact for easy installation

Take advantage of Genasun's advanced MPPT technology and enjoy more reliable power from smaller panels.



**+10%**

additional power  
in the summer.  
No panel is too  
hot to handle.



**+30%**

more power on  
those shorter,  
colder winter days.



**+50%**

increase in  
energy harvest  
from partially  
shaded panels.

Typical power gains from Genasun MPPT controllers vs the best PWM controllers available.



[www.genasun.com](http://www.genasun.com) Sold through Blue Sky Energy  
(760) 597-1642 [sales@blueskyenergyinc.com](mailto:sales@blueskyenergyinc.com)

# Specifications:

## GV-4-Pb-12V

Maximum Recommended Panel Power:	50W
Rated Battery (Output) Current:	4A
Nominal Battery Voltage:	12V
Max Panel Voltage (Voc):	27V
Recommended Max Voc at STC:	22V
Minimum Battery Voltage for Operation:	7.2V
Input Voltage Range:	0-27V
Recommended Maximum Input Short Circuit Current (for Solar Use):	4A
Maximum Input Current *:	7A
Charge Profile:	Multi-Stage with Temperature Compensation
Absorption Voltage:	14.2V
Absorption Time:	2 Hours
Float Voltage:	13.8V
Charging Output Voltage Range:	7.2-18V
Battery Temperature Compensation:	-28mV/°C
Operating Temperature:	-40°C - 85°C
Maximum Full Power Ambient:	50°C
Electrical Efficiency:	96% - 99.85% typical
Tracking Efficiency:	99% typical
MPPT Tracking Speed:	15Hz
Operating Consumption:	0.125mA (125uA)
Night Consumption:	0.9mA (90uA)
Marine Grade:	Yes
Connection:	4-position terminal block for 12-30AWG wire
Weight:	2.8 oz., 80 g
Dimensions:	4.3 x 2.2 x 0.9", 11 x 5.6 x 2.5 cm
Warranty:	5 years

\*Maximum current that the controller could draw from an unlimited source.

Copyright © 2015 Blue Sky Energy. All rights reserved. Changes are periodically made to the information herein which will be incorporated in revised editions of this publication. Blue Sky Energy may make changes or improvements to the product(s) described in this publication at any time and without notice.