

# RAFALE

## TEST ITS SAFETY

**GUARANTEE**  
**2 years**

Parts and  
labour

### PRACTICABILITY

With its specially designed foldable fixing hook, the operator can easily rest the equipment on the workstation as required.

### SAFETY

There is no danger of burns since the RAFALE's nozzle is developed in aluminium and surrounded with a double protection. This means that it always stays warm, regardless of the duration and intensity of use.

### VERSATILITY AND INGENUITY

Burners rotating through 360°, **even more robust and can be disconnected in just 1 click**, guaranteeing the ability to operate in all working positions.

### COMFORT

Weighing in at just over 1 kg, RAFALE has been designed to limit user fatigue as much as possible. The challenge has been met with a successful combination of ergonomics and comfortable noise levels (88 dBA at a distance of 1 m).

### CONTROL

With its security handle, you control RAFALE... RAFALE doesn't control you ! When the handle is released, RAFALE stops!

### SIMPLICITY

With its high resistance treated steel fast swivel connection, tangled hoses and premature wear are things of the past, while working efficiency is enhanced with its 13 or 35 kg propane cylinders.

### RELIABILITY

With its integrated «Piezo» ignition, RAFALE always starts when you want... immediately.



### PERFORMANCE

With two power levels, RAFALE adapts to the most demanding working environments while always offering adjustable heating power, which can be strictly adjusted to meet the needs of each user.

CE  
1312

**EXPRESS**  
depuis 1905

**Shrink wrapping**



**PALLETISATION**



**WINTER STORAGE**



**CONTAINMENT / SCAFFOLDING**

**GUARANTEE**  
**2 years**

Parts and  
labour



## THE CASE CONTAINS

### Hot air gun RAFALE

1 regulator holder adjustable between 1.5 and 3.5 bar  
10-metre rubber hose compliant with **ISO 3821**

1 instruction manual

1 pair of gloves

1 heat deflector [Cat. No. 4065]

1 spare piezo

|                                                   | RAFALE                                           | RAFALE +                                          |
|---------------------------------------------------|--------------------------------------------------|---------------------------------------------------|
| ENERGY SOURCE                                     | Propane                                          | Propane                                           |
| WORKING PRESSURE<br>(bar - psi)                   | 1.5 to 3.5 bar<br>22 to 51 psi                   | 1.5 to 3.5 bar<br>22 to 51 psi                    |
| ADJUSTABLE POWER<br>(1.5 → 3.5 bar - 22 → 51 psi) | Between 24 and 43 kW<br>82 000 and 147 000 BTU/h | Between 37 and 65 kW<br>127 000 and 222 000 BTU/h |
| POWER                                             | 40 kW - 137 000 BTU/h                            | 65 kW - 222 000 BTU/h                             |
| GAS CONSUMPTION<br>(kg /h - lb/h)                 | Between 1.8 and 3 kg /h<br>4 and 6.7 lb /h       | Between 2.7 and 4.8 kg /h<br>7 and 10.6 lb /h     |
| WEIGHT (kg - lb)                                  | 1.170 kg approx - 2.580 lb                       | 1.170 kg approx - 2.580 lb                        |
| AIR CONSUMPTION<br>(m³/h)                         | Between 28<br>and 45 approx                      | Between 48<br>and 72.2 approx                     |
| SAFETY DEVICE                                     | Security handle<br>with protection               | Security handle<br>with protection                |
| EXCESS OUTPUT                                     | Excess output<br>regulator valve                 | Excess output<br>regulator valve                  |
| ADAPTABLE<br>EQUIPMENT                            | Heat deflector (option)                          | Heat deflector                                    |
| NOISE LEVEL (dBA)                                 | < 83                                             | 85 - 88                                           |
| CERTIFICATION                                     | CE 1312                                          | CE 1312                                           |

Distributor stamp