



# SUPERIOR ECO TILES®

AUSTRALIAN MADE INNOVATIVE DESIGN



## Features & Benefits



Australian made from UV resistant PP



Slip and fire resistant, chemical and hydrocarbons resistance



Perforated decking surface lets sunlight through to preserve the flora and fauna



Load rating (per square metre) of 5kPa



High force resistance against impact and static loads



Suitable for existing and new gangways, pontoons and platforms.



Extremely resistant to weather conditions



Tested to comply with AS1657-20018



Easy and quick to install and dismantle if required



Aesthetically pleasing

Contact our team of friendly experts today.

 +61 7 5594 8200

 [sales@superiorjetties.com](mailto:sales@superiorjetties.com)

 [www.superiorjetties.com](http://www.superiorjetties.com)

**WSW**  
WALK ON WATER



**SUPERIOR**  
JETTIES®



# SUPERIOR ECOTILES®

AUSTRALIAN MADE INNOVATIVE DESIGN

## Accessories & Dimensions



Decking tile fixing full circle (in between 4 tiles)



Decking tile fixing half circle (in between 2 tiles)



Decking tile quarter circle (end cap)



Connection screw for fixing to aluminium



Connection screw for fixing to timber



Tile to tile connection peg (2/tile to tile connection)



Size: 495mm x 595mm x 50mm +3



Weight: 3.0kg



Standard colour: Pontoon Grey



Load rating: 5kPa



Contact our team of friendly experts today.

+61 7 5594 8200

[sales@superiorjetties.com](mailto:sales@superiorjetties.com)

[www.superiorjetties.com](http://www.superiorjetties.com)